



SITRAK-G5S

6x4 Cargo Cab & Chassis



SPECIFICATIONS G5S 6x4 LWB

ENGINE

330 hp Euro 6 German Technology MC07H.33-61

Type: 6-cylinder 24 valve SOHC


Total Displacement: 7.360 litre

Power Rating: 240 kw @ 2200 rpm

Maximum Torque: 1322 Nm @ 1200-1700 rpm

Emissions Technology: Selective Catalytic Reduction and Diesel Particulate Filter

Exhaust: Catalytic muffler with SCR catalyser and Diesel Particulate Filter



TRANSMISSION

6-speed Allison Automatic

Model: 3200P Series

Type: 6 Speed Automatic

Forward Ratio: 3.49, 1.86, 1.41, 1.00, 0.75, 0.65

Reverse Ratio: 5.03

Operation: 2-pedal operation with automatic and manual shift control

CHASSIS

Type: Ladder frame

Dimensions: 280 x 80 x 8 mm steel channel

Chassis Width: 940mm (front)

850mm (rear)

Front Underrun Protections (FUP)

STEERING

Type: Bosch HD steering gear with gear driven pump

Gear Ratio: 22.20~26.20:1

Wheel Lock Angle: 43.0° (inside), 33.0° (outside)

FRONT AXLE & SUSPENSION

Type: VPD71DS (Disc)

Capacity: 7.0 tonne

Suspension Type: Non-Independent 3 parabolic leaf springs with hydraulic shock absorbers

REAR AXLE & SUSPENSION

Type: MCY11BES (Disc)

Capacity: 18.0 tonnes

Ratios: 4.63 (optional: 3.08, 3.36, 3.7, 4.11, 5.29)

Suspension Model: Sinotruk Air Ride

Type: 8 bag with ECAS to control ride height

Differential: Driver controlled inter-axle lock and differential lock

BRAKES

Type: Full air front and rear disc brakes

Control: Wabco EBS/ESC/ASR

Park Brake: Spring Brake acting on axle 2 & 3

Auxiliary Braking: Air controlled exhaust brake

Front Diameter: 430 mm disc

Rear Diameter: 375 mm disc

FUEL CAPACITY

6x4 LWB: 300 litre rectangular aluminium tank (RHS)
45 litre AdBlue tank (LHS)

ELECTRICAL SYSTEM

Type: Double/Control Positive Pole

Voltage: 24 Volt

Batteries: 2 x 12V 180 Ah (1080CCA) with isolator switch

Alternator: 28 Volt – 110 Amp

Starter: 24 Volt – 5.5 kW

350 Amp Anderson Plug

CAN bus access plug for telematics (optional)

WHEELS & TYRES

Wheel Type: 10-stud 335 mm alloy

Rim Size: 22.5x9.0 (front)

22.5x8.25 (rear)

Tyres: 295/80 R22.5 (front)

11R22.5 (rear)

Tyre Rating: 14,200 kg at 130 PSI (front)

23,200 kg at 125 PSI (rear)



CAB FEATURES

- 90° opening doors with electronically operated windows
- Anti-slip steps
- Auto windscreen wipers with two speed selection and adjustable intermittent mode
- Central locking and immobiliser
- Class V and Class VI mirrors (LHS kerb and front kerb mirrors)
- Cornering fog lamps
- Daytime Running Lights (DRL)
- Electrohydraulic cab tilt
- Exterior temperature sensor
- Four-point cab mounting system with air bag suspension
- Heated and electric exterior mirrors with independent convex "spotter" mirror
- Sunroof
- Translucent sun visor

CAB INTERIOR FEATURES

- 12.2" Multimedia touchscreen Radio/Wi-Fi/Bluetooth and steering wheel controls
- 360° Birdseye view camera: front, rear and side facing including recording
- Air adjusted tilt and telescopic steering wheel
- Apple CarPlay
- Automatic climate control
- Centre console fridge/freezer (optional)
- Courtesy and reading lights
- Fully adjustable ISRI self-levelling air suspension driver's seat with headrest, armrest, heated and ventilated, adjustable damper and integrated lap-sash retractor seat belt
- Interior LED trim lighting
- Overhead storage compartments, push out tray, cupholders and door pockets.
- USB and cigarette lighter power outlets

DRIVER CONTROL FEATURES

- Air horn switch
- Combination switches controlling exhaust brake, manual gear selection, turn indicators and windscreen wipers
- DPF regeneration and override buttons
- Fuel primer switch (automatic off)
- Hazard lights
- Headlight levelling switch
- Rotary style gear selector

ADVANCED SAFETY FEATURES

- Automatic Emergency Braking (AEB)
- Blind Spot Camera (turn signal triggered)
- Front Collision Warning System (FCWS)
- Hill Start Assist (HSA)
- Lane Departure Warning (LDW)

DIGITAL CLUSTER

- AdBlue gauge
- Air Pressure gauges (tank 1 and tank 2)
- Coolant temperature
- Driver profiles
- DPF filter gauge
- Engine hour meter
- Fuel consumption
- Fuel gauge
- Multimedia display
- Speedometer with digital read out
- Tachometer
- Transmission oil life
- Transmission oil level
- Trip meter

WARRANTY AND ROADSIDE ASSISTANCE

Standard Factory Warranty* (whichever comes first):

3 years or 600,000km

Driveline Warranty (whichever comes first):

3 years or 1,000,000km

Warranty on Dealer Fitted Accessories:

12 months unlimited kilometres



*Warranty on batteries is 12 months from delivery date

DIMENSIONS



Measurements in mm/Weights in kg

Chassis Model		G5S 6x4 LWB
Overall length (OAL)		11,030
Nominal Body Length (CA+WBx0.6 -100)		9,440
Front Overhang (FOH)		1,430
Wheelbase (WB)		6,300
Bogie Axle Spread (AS)		1,400
Rear Overhang (ROH)		3,300
Cab Overhang (COH)		460
Cab to Axle (CA)		5,840
Cab to Rear (CR)		9,140
Front Track (FT)		2,035
Rear Track (RT)		1,850
Outer Rear Track (ORT)		2,493
Ground Clearance [^]	Front	285
	Rear	250
Turning Circle	Kerb to Kerb	21,894
	Wall to Wall	23,746
Approach Angle (°)		17
Departure Angle (°)		12
Cab Height (OAH) [^]	Unladen height	3,145
	Laden Height	3,075
Cab Width (CW)		2,240
Front Suspension Height [^]	Unladen	1,048
	Laden	978
Rear Suspension Height [^]	Unladen	1,020
	Laden	1,000
Rear Frame Height (RFH) [^]		1,005
Chassis Width		850
Mass Rating	GVM	25,000
	GCM	TBC
Chassis mass front [#]		3,820
Chassis mass rear [#]		3,540
Chassis mass total [#]		7,360

*Nominal body length calculated at maximum 3.7m rear overhang

[^]Measurement based on front axle tyres 295/80R22.5 and rear axle tyres 11R22.5

[#]Weights are to standard configuration and include cab chassis with no driver and 10L of fuel



All efforts have been made to ensure the information contained in this brochure was correct at the time of printing or uploading. Rumble Auto Pty Ltd reserves the right to alter any specifications, features, or equipment details without prior notice. To the extent permitted by law, Rumble Auto Pty Ltd accepts no liability for any loss or damage arising from reliance on the information contained in this brochure. Please consult with Rumble Auto Pty Ltd at the time of ordering to confirm the availability of colours, specifications, equipment, design features, and options for your selected vehicle. Note that some options may only be available in combination with others. Up-to-date information on accessories, features, pricing, and availability is available upon request.